Spec	Yes	No
Body		
PL1415SD(12.4/15.5) 14', 40" Side Height with 55" Tailgate height -		
Side Tilt Indicator		
Coal Door - CENTER		
12" Asphalt Apron		
1/2 Cabshield 24" Corten		
ON10019 - Bar Flights every link		
Step Inside Body		
Step Over Gearbox		
Ladder Handles		
18" Spinner Disc		
86" Inside Width, 98" Outside		
Stainless Steel Sides, Ends & Cabshield		
1/4" Hardox 450 Tipper Floor		
25:1 Wormgear Gearbox		
Double Acting Tailgate		
Solid Curb Sidewall		
Ladder Front Left		
Remote Grease		
Shovel Holder		
Mud Flaps & Hangers front & rear of Tandem		
Mud flap at rear of fuel tank - Salt Protection		
Lighting & Rear of Truck		
Lighting and Rear of Truck		
Heated LED snowplow Lights		
LED Wing Light		
LED Sander Light		
LED oval flashing lights back of body		
Incandesent Back Up Lights - back of body		
Swivel gladhands at air connections rear of truck		
LED Strobe Lights Mounted to the Front & Sides of the Cabshield		
Heated LED Roof Lights - Hi/Low Beam - 2 Switches in the Cab		
GoLight - Wireless Controller, Roof Mounted		
Bolt On Pintle plate & Hook (25 ton) and Cross Member, "D" rings, Relocate OEM Glad		
Hands & Electrical Plug		
Bolt On Removable Chipper Bar		
		!
Plow Equipment		
Custom Hitch Plow Mount-Power Tilt (incl. yoke)		
4" x 10" DA Cylinder (cannot be used with Husting Hitches)		
Front Mast FH33 Hydraulic Assembly w/mtg. 66" of benching height		
5" extension pads (pair)		

Standard Non Tilting front wing hinge		
1/2" wire rope cable (for use with Hydraulic (FH - FAH) Front Mast) for all H600 & H700		
(single) Model Rear Masts except H712ER		
Rear Mast assembly (RH) includes poly cyl & valve box covers		
40 Gallon (RH) Cabinet Mount (for H600 & H700 Series Rear Mast)		
Low Oil Sensor (for cabinet tank) w/dash warning light		
Rear mast cable wing stop.		
One Way (RH) moldboard 3564HSE9 (nose 35" - Discharge 64")		
Quick hitch Front plow connection		
30-1/2" pushlug swivel (cannot be used with 4572 one way)		
#65 Adj. Pushframe Shoes, Alloy (pair)		
Moldboard Shoe 45 degree (1 pc.)		
144WHD RH wing weldment-12' long blade takes 11' Steel cutting edge		
10 deg. fab. wing shoes		
Standard Stand off Arms		
Hydraulics		
Front Mount PTO/Pump		
6 Spool Valve (dump, side tilt, plow, wing toe, heel, slide)		
5 bank pneumatic air kit, tubing, fittings, pressure protection valve		
Swivel pedistal floor mount for plow and wing levers		
4 Handle Pedestal Mount (control for plow & wing functions)		
2 Handle Floor Mount (control for dump & side tilt)		
Electric Salter Controller		
SCE2UL1407AR spin-a-veyer valve, (conveyor floor & spinner valving)		
Protective steel enclosure for Spin-A-Veyer valves		
Hyd Oil Line Shut Off (each) 2"		
Second hydraulic filter return line from body functions to hyd. tank		
Second Hydraulie Interview I on Seay (and solo is to Hydraulie		
Tarp System	<del></del>	
Roll-Rite Double Arm Tarp System		
Asphalt Tarp		
Camera System		
Dash Mount Monitor, Camera Mounted On Cabshield with View of Inside the Dump		
Body		